

Three-phase asynchronous motor

MOTOR FRAME: **Aluminium**

a company of



Motor type: **WU-DA90LWX IE2 6P 1,1KW B3**
 Motor item number: **090W227601T**

Rated power:	1,1 kW			50 HZ data	60 HZ data	kW
Poles(Synch speed):	6p (1000) r.p.m					r.p.m
Full load speed:	925 r.p.m					r.p.m
Voltage:	230	/	400	V		V
Frequency:	50 Hz					Hz
Connection:	Δ	/	Y			
Amps full load (FLA):	5,3	/	3	A		A
Amps no-load (NLA):				A		

Enclosure:	IP55		Cable entries size:	1 x CM20	
Mounting:	IM B3 (IM 1001)		Winding protection:		
Insulation Class:	F		Max. Altitude:	1000	m.a.s.l.
Max. ambient temp.:	+40	°C	Heater:	no	
Min. ambient temp.:	-20	°C	Shaft extension:	24x50	mm
Max. temp. rise:	80	K	Weight:	14,5	kg
Duty type:	S1		Painting:	Alkyd-Amin Resins Paint	
Cooling form:	IC411 (TEFC)		Color:	RAL 5021	
Bearing DE	6205	ZZ CM	Box position:	Top DE	
Bearing NDE	6203	ZZ CM	Cable entry towards:	Right	
Grease:	Lithium or Polyurea Base		Cable type:	N/A	
Regreasing facilities:	NO		Balance grade:	Normal	

Efficiency class:	IE2			Sound pressure (1m):	65 dB(A)
Load data:	100%	75%	50%	Resistance R20:	5,21 PH
Efficiency:	78,1	75,6	73,1		
Power factor:	0,67	0,57	0,42		

Full load torque (FLT):	11,4	Nm	Pull out torque ratio:	3,0	MK/MN
Starting torque ratio:	3,0	MA/MN	Pull up torque:	2,6	MS/MN
Starting current ratio:	4,8	IA/IN	Rotor inertia WK2:	0,0043	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:	
Certificate number:	t _E time:	sek

Special remarks: